

EXODUS TEMP

ONE BOX SOLUTION TEMPORARY LED EXIT LIGHT

This low maintenance, wall or ceiling mountable one box solution Exit Sign comes complete with all variations of the Running Man pictogram and offers many years of reliable, succinct and efficient Exit Lighting.

Its no-frills slide and connect style installation mechanism and robust design allows it to be used in a wide variety of indoor applications, ranging from offices through to retail stores, cafes, schools and public spaces in the quickest time possible.






















Technical Specifications

| Item | Part Number | TMP-EXIT | | |
|-------------------------|--|---|--|--|
| | Description | LED Slide and Connect 24m Temporary Exit Light c/w Synthium™ Battery | | |
| | | | | |
| Input | Voltage & Frequency | 230VAC ; 50Hz | | |
| | Installation | Large terminal block and 20mm ² cable entry | | |
| Output | Light Source | High efficacy LED strip, 100,000 hours | | |
| | Mode of Operation | Maintained | | |
| | Power Consumption | 2W (standby) | | |
| | Emergency Duration | > 120 minutes | | |
| | Lineigency bulation | > 120 Hillington | | |
| Controls | Charger | Intelligent 3-stage charger with <i>Synthium™</i> battery management system | | |
| | Protection | Overcharge, low voltage disconnect, overcurrent, short circuit | | |
| | Testing Facility | Manual test switch | | |
| | Indicators | Battery charger green LED | | |
| Physical | D''' | | | |
| | Diffuser | All variations of Running Man pictogram | | |
| | Construction | Flame-retardant polycarbonate | | |
| | Mounting | Surface mounted - wall or ceiling (single or double side application) | | |
| | | | | |
| | Dimensions L x W x H | 360mm x 60mm x 215mm | | |
| | Dimensions L x W x H IP Rating | 360mm x 60mm x 215mm IP 20 | | |
| | | | | |
| | IP Rating Weight | IP 20 1.2kg | | |
| Environment | IP Rating Weight Operating Temperature | IP20 1.2kg 1° to 40°C | | |
| Environment | IP Rating Weight | IP 20 1.2kg | | |
| | IP Rating Weight Operating Temperature | IP20 1.2kg 1° to 40°C | | |
| Environment Compliance | IP Rating Weight Operating Temperature Relative Humidity | IP 20 1.2kg 1° to 40°C 0 to 95% | | |
| | IP Rating Weight Operating Temperature Relative Humidity Standards | IP 20 1.2kg 1° to 40°C 0 to 95% RCM / EMC, AS/NZS 2293, AS/NZS 60598.1 | | |

NOTE: Product specifications subject to change without prior notice due to ongoing product improvement policy and changes to industry standards.

Dimensions



AS/NZS 2293.1:2018 Spacing Table

This product performs the dual role as an 24m Exit Sign and an Emergency luminaire with the following NATA-accredited emergency classifications:

| SPACING TABLE | | MOUNTING HEIGHT (m) | | | | | |
|--|------------|---------------------|-----|-----|------|--|--|
| NATA Classification | | 2.1 | 2.4 | 2.7 | 3.0* | | |
| TMP-EXIT | C0 - D3.2 | 6.5 | 6.5 | 6.5 | 6.5 | | |
| | C90 - D2.5 | 5.8 | 5.8 | 5.7 | 5.6 | | |
| * Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2018 | | | | | | | |

Distributed By:







