


EXODUS[™] **BLADE**

**ONE BOX SOLUTION - RECESSED
MAINTAINED LED BLADE EXIT LIGHT**

The Exodus[™] Blade is a sleek and aesthetically-pleasing recessed edge-lit Exit Light that provides a touch of class and elegance to enhance the look and feel of any premium interior space.

Its ease of installation and stylish Running Man pictogram positions this product more towards internal spaces with high customer-visibility such as apartments, public buildings, offices and retail outlets.



Available as:



SYNTHIUM[™] nanotechnology is an advanced environmentally sustainable energy development that offers extended battery life, low cost of ownership, enhanced performance and improved safety.




Technical Specifications

Item	Part Number	EXS-BLADE
	Description	LED One Box Solution Recessed Mounted Blade Exit Light c/w <i>Synthium™</i> Battery
Input	Voltage & Frequency	230VAC ; 50Hz
	Installation	Complete with 1.2m flex cable and plug
Output	Light Source	High performance LED bar, 100,000 hours
	Mode of Operation	Maintained
	Power Consumption	2W (standby)
	Emergency Duration	> 120 minutes
Controls	Charger	Intelligent 3-stage charger with <i>Synthium™</i> battery management system
	Protection	Overcharge, low voltage disconnect, overcurrent, short circuit
	Testing Facility	Manual test switch
	Indicators	Battery charger green LED
Physical	Battery	<i>Synthium™</i> Lithium Iron Phosphate - 10 year design life
	Diffuser	All variations of Running Man pictogram
	Construction	Flame-retardant polycarbonate
	Mounting	Recessed mounted, 380mm x 75mm cutout, adaptor plate to suit larger cutouts available
	Dimensions L x W x H	440mm x 100mm x 200mm
	IP Rating	IP20
	Weight	1.5kg
Environment	Operating Temperature	1° to 40°C
	Relative Humidity	0 to 95%
Compliance	Standards	RCM / EMC, AS/NZS 2293, AS/NZS 60598.1
	AS/NZS 2293 Classification	C0 D6.3 C90 D3.2
Accessories	STAR™ Self-Test and Reporting	P/N: EXS-BLADE/ST
	DALI-compatible	P/N: EXS-BLADE/DL
	SYNECTIX™ RF Wireless	P/N: EXS-BLADE/RF
	Replacement Battery	P/N: BAT-BLADE: <i>Synthium™</i> LiFePO ₄

NOTE: Product specifications subject to change without prior notice due to ongoing product improvement policy and changes to industry standards.

Dimensions



Spacing Table

This product performs the dual role as an 24m Exit Sign and an Emergency luminaire with the following NATA-accredited emergency classifications:

SPACING TABLE	MOUNTING HEIGHT (m)			
NATA Classification	2.1	2.4	2.7	3.0*
C0 - D6.3	8.5	8.8	8.9	9.1
C90 - D3.2	6.5	6.5	6.5	6.5

* Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2018.

Distributed By:

